

638311 ONTARIO INC., O.A.

WAUBAUSHENE MACHINE & WELDING

Box 99, 111 Coldwater Rd., Waubaushene, Ontario, L0K 2C0, Canada
Phone: (705) 538-1459 or (800) 663-1624 Fax: (705) 538-1776



LD125-2T

Double Tank System -> No Dead Time

Standard Equipment:

Motor: 2x 1 ½ Hp electric

Tank: 2x 115 US Gal. (2x 435 l)

Connections: 2" NPT intake with motorized ball valve / 2" NPT discharge with motorized ball valve

Finish: painted white or blue metallic top, hot dipped galvanized cycle tanks

Included Accessories: none

Control Box Approval:



- Features:**
- ✓ auto cycling between suction and discharge as necessary
 - ✓ constant vacuum - automatic shut off for motor when max. vacuum is reached -> pump can be left turned on all day, vacuum will be available instantly when needed
 - ✓ constant flow - one tank is always ready for suction -> no dead time
 - ✓ probe error warning sensor
 - ✓ odourless - odour is vented to discharge line
 - ✓ easy single switch operation (OFF / Suction / Discharge)
 - ✓ indicator lights to monitor pump mode (Suction / Discharge / Probe Error) & tank status (Empty / Full)
 - ✓ required power: 208-230V AC + Neutral, 30Amp. circuit min., 60 Hz (other voltages available)

Optional Equipment:

- x remote box or galvanized remote stand for multiple intake locations on dock (including electric controls)
- x token, coin, \$-bill or card reader operation
- x dual coated tank (galvanized & painted)
- x single hand operated suction nozzle

Performance Specifications:

Max. Suction Lift (recommended)	20 ft (6 m)	Max. Discharge Head	30 ft (9 m)
Max. Suction Distance (recommended)	1500 ft (450 m)	Max. Discharge Distance (recommended)	2000 ft (600 m)
Max. Suction Performance*	90 GPM (340 l/min)	No. of Boats serviceable at same Time	2

* performance (in US gallons/minute) through 2" port @ 0 ft vertical lift, 1725 rpm

Dimensions:

Width	64" (163 cm)	Length	72" (183 cm)
Height	70" (178 cm)	Tank Diameter	30" (76 cm)
Empty Weight	1100 lbs (500 kg)	Full Weight	3055 lbs (1390 kg)
Intake Port	2"	Discharge Port	2"

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

PLEASE VISIT OUR WEBSITE WWW.WMWPUMP.COM FOR MORE INFORMATION

15.04.06