

# WAUBAUSHENE MACHINE & WELDING

## Pump Specifications 2006



### Stationary Pumpout Systems

Model	AVR20	AVR60	AVR125	CVP60	LD125	LD240	LD125C	CHR300	CHR600
Width	20"	34"	34"	38"	34"	36"	42"	36"	48"
Length	44"	38"	60"	43"	60"	72"	60"	85"	88"
Height	34"	48"	48"	48"	50"	55"	50"	55"	66"
Approx. Weight Empty / Full	200 lbs / 425 lbs	350 lbs / 905 lbs	460 lbs / 1440 lbs	400 lbs / 955 lbs	550 lbs / 1530 lbs	890 lbs / 2800 lbs	700 lbs / 1680 lbs	1700 lbs / 3825 lbs	2500 lbs / 7775 lbs
Connection Intake / Discharge	1 1/2" / 1 1/2"	2" / 2"	2" / 2"	2" / 2"	2" / 2"	2" / 2"	2" / 2"	3" / 3"	3" / 2 or 3"
Max. Suction Lift (recommended)	20 ft	20 ft	20 ft	20 ft	20 ft	20 ft	20 ft	20 ft	20 ft
Max. Discharge Head	30 ft	30 ft	30 ft	30 ft	30 ft	30 ft	120 ft	30 ft	30 ft
Max. Suction Distance (recommended)	100 ft	250 ft	250 ft	250 ft	1500 ft	1500 ft	1500 ft	3000 ft	3000 ft
Max. Discharge Distance (recommended)	250 ft	500 ft	500 ft	500 ft	2000 ft	2000 ft	2000 ft	3000 ft	3000 ft
Max. Suction Performance <sup>1</sup>	20 GPM	50 GPM	50 GPM	50 GPM	90 GPM	90 GPM	90 GPM	200 GPM	200 GPM
# of Boats simultaneously <sup>2</sup>	1	1	1	1	2	2	2	4	4
Motor Power	1/4 HP	3/4 Hp	3/4 Hp	3/4 Hp	1 1/2 Hp	1 1/2 Hp	1 1/2 Hp	3 Hp	3 Hp
Available Power Configuration	a, b, d	a, b, d	a, b, d	a, b, d	a, b, c, d	a, b, c, d	b, c, d	b, c, d	b, c, d
Pump Tank Size <sup>3</sup>	25 Gal.	65 Gal.	115 Gal.	65 Gal.	115 Gal.	220 Gal.	115 Gal.	250 Gal.	620 Gal.
Control Box Approval									

### Power Configurations:

- a: 120 VAC, 60 Hz
- b: 208-230 VAC, 60 Hz (single phase)
- c: 208/230V VAC, 60 Hz (three phase)
- d: 230 VAC, 50 Hz

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

1 Max. performance (in US Gallons / Minute @ 0 ft lift, 1725 rpm) through full intake port.  
 2 Bigger models could serve more than one boat simultaneously (based on their max. suction performance).  
 3 Pump cycle tank in US Gallons



### Mobile Pumpout Systems

Model	DPK20E	DPK125	DPK240	DPK240E
Width	27"	30"	36"	36"
Length	70"	60"	72"	72"
Hight	38"	56"	60"	53"
Approx. Weight Empty / Full	200 lbs / 425 lbs	440 lbs / 1440 lbs	800 lbs / 2700 lbs	800 lbs / 2700 lbs
Connection Intake / Discharge	1 ½" / 1 ½"	2" / 2"	2" / 2"	2" / 2"
Max. Suction Lift (recommended)	20 ft	20 ft	20 ft	20 ft
Max. Discharge Head	30 ft	30 ft	30 ft	30 ft
Max. Suction Distance (recommended)	100 ft	500 ft	500 ft	250 ft
Max. Discharge Distance (recommended)	250 ft	1000 ft	1000 ft	500 ft
Max. Suction Performance <sup>4</sup>	20 GPM	90 GPM	90 GPM	50 GPM
# of Boats simultaneously <sup>5</sup>	1	2	2	1
Motor Power	¼ Hp	3 Hp	3 Hp	¾ Hp
Available Power Configuration	a, b, d	Gas Engine	Gas Engine	a, b, d
Pump Tank Size <sup>6</sup>	25 Gal.	115 Gal.	220 Gal.	220 Gal.
Control Box Approval	c 	n/a	n/a	c 

#### Power Configurations:

- a: 120 VAC, 60 Hz
- b: 208-230 VAC, 60 Hz (single phase)
- c: 208/230V VAC, 60 Hz (three phase)
- d: 230 VAC, 50 Hz

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

4 Max. performance (in US Gallons / Minute @ 0 ft lift, 1725 rpm) through full intake port.  
 5 Bigger models can serve more than one boat simultaneously (based on their max. suction performance).  
 6 Pump cycle tank in US Gallons